

Swarf & emulsions vacuum cleaner 3,6 kW - Tilting chassis with swarf basket



High performance industrial vacuum cleaner

High quality standards – well construed bypass- suction aggregates, silenced turbo fan.

Liquid level control through the liquid level-/draining hose.

Robust and smooth-running chassis for **high mobility**. Compact, modular design with high quality stainless steel dirt container (**V2A**).

The **swarf basket** in the dirt container separates solid materials and liquids. The swarfs drop into the swarf basket. The emulsions trickle down into the dirt container and can be removed through the liquid level-/ **draining hose**.

Tilting chassis for the easy removal of the dusts

Liquid repellent cartridge filter prevents suction of oil mist and dust.

360° swivelling suction bend with Kamlock-coupling for safe connection of the suction hose. Length of cable: 8 m

Optional:

Electronic liquid level control

| Model | | EP 1236-140 |
|----------------------------------|-------------------|-------------|
| Voltage | Volt | 230 |
| Power output | Watt | 3.600 |
| Max. air flow rate | m ³ /h | 490 |
| Max. neg. pressure | mbar | 210 |
| Filter surface | m ² | 1,0 |
| Container | ltr. | 140 |
| Swarf basket (height-adjustable) | ltr. | 60 |
| Type of protection | | IP 33 |
| Suction connection | Ø mm | Camlock-50 |
| Dimensions | cm | 50x65x105 |
| Weight | kg | 80 |
| | Art.-no. | 151-2010 |

Included in the delivery: 3,5 m PUR- suction hose dia. 50 mm and crevice nozzle

Details EP 1236-140

① Motorhead with swivelling suction bend

Motorhead with separately switchable motors as well as 360° swivelling suction bend with Kamlock-coupling.
(Similar to illustration)

② Container

The container of the wet vacuum cleaner can be taken off the undercarriage.

③ Tilting chassis

For easy disposal the container can be tilted in the undercarriage without any strain.

④ Draining hose

Liquids can be removed easily through the draining hose

⑤ Swarf basket

The integrated swarf basket separates solid material from liquids. The swarfs remain at the bottom. The liquids trickle down into the container and can be removed through the draining hose.

⑥ Container

For complete draining of the container the liquid level control-/ draining hose is welded on the bottom of the container.



1



2



3



4



5



6

EVOTEC – Accessory sets



Machine cleaning set

optimised for cleaning production machines.
Consisting of bulk suction nozzle, beveled tube rubber nozzle, pointed rubber nozzle and round brush nozzle



dia. 40 mm = **052-1080**

dia. 50 mm = **052-1070**



Industrial floor cleaning set

for cleaning all floors. Consisting of multi-part hand tube, **metal revolving nozzle with brush strip** and **replacement rubber strip**, round brush nozzle



dia. 40 mm, working width 370 mm = **052-1030**

dia. 40 mm, working width 450 mm = **052-1035**

dia. 50 mm, working width 370 mm = **052-1040**

dia. 50 mm, working width 450 mm = **052-1050**

dia. 50 mm, working width 500 mm = **052-1060**



Set for cleaning at height

Consisting of 2 m hand tube, curved tubular nozzles 100 mm and 200 mm, one wall nozzle and one floor nozzle

dia. 40 mm = **052-1090**

dia. 50 mm = **052-1100**